

Water EXCELLENCE...

Pump PERFECTION...



AN ISO 90001 : 2015 CERTIFIED COMPANY

AQUA1

Submersible Pumps | Panels | Cables

— Trust the flow —

AQUA PUMPS & ENGINEERING

H.O. : Opp. Gokul Park,
Kothariya Main Road
Rajkot, Gujrat - 360003

OUR OTHER PRODUCTS :

Self Priming Pumps, Shallow Well Pumps, Monoblock Pumps,
Induction Motors, Submersible Cables & Submersible Panels.

AN ISO 90001 : 2015 CERTIFIED COMPANY

AQUA1

Submersible Pumps | Panels | Cables

— Trust the flow —



Agriculture Use



Industrial Use



Urban Development

Aqua Pump & Engineering



AQUA1
Submersible Pumps | Panels | Cables
—Trust the flow—

V3 Submersible Pump Set (68 MM & 74 MM)

SALIENT FEATURES

1. Fully stainless steel stator tube
2. All the diffusers and impellers are glass Engineering Plastic.
3. Rotor are grinded & burnished to give better surface finish value which ensure long life
4. Start Easily at low voltage

TECHNICAL SPECIFICATION

Head Range	: 8 To 109 Meter
Discharge Range	: 10 to 90 LPM.
Motor Rating	: 0.5HP to 1.5HP, 220V, 50Hz, AC Supply
Voltage Range	: 160V to 240V

V4 Submersible Pump Set

SALIENT FEATURES

1. International NEMA/MESH spline coupling.
2. Rotors are dynamically balance to minimise noise & vibration.
3. Pump & motors are in fully stainless steel design.
4. All the pumps are supply with guide bush at suction end along with sand protection.

TECHNICAL SPECIFICATION

Head Range	: 5 to 413 meter
Discharge Range	: 12 to 485 LPM
Motor Rating	: 0.5HP to 5.0 HP in Single Phase-230V, 50Hz, AC Supply 0.5HP to 7.5HP in Three Phase-380V/415V, 50Hz, AC Supply
Voltage Range	: 160V to 250V (1 Phase) 350V to 440V (3 Phase)



AQUA1
Submersible Pumps | Panels | Cables
—Trust the flow—

V6 C.I. (Radial/Mix flow) Submersible Pumpset

SALIENT FEATURES

1. Robust construction to ensure durability of pumpset.
2. Winding wires are wrapped with superior polymer to withstand wide voltage fluctuation.
3. All the rotating parts are dynamically balance to reduce vibration & noise.
4. Rotors are painted with special epoxy paint for long life.

TECHNICAL SPECIFICATION

Head Range	: A) Radial flow-14 to 238 meter B) Mix Flow 9 to 108 meters
Discharge Range	: A) Radial flow-50 to 780 LPM B) Mix Flow-200 to 1150 LPM
Motor Rating	: 3.0 HP to 20 HP in three phase, 300v/350v/380/415v/50Hz, AC Supply 3.0 HP to 7.5 HP in single phase, 230V/50Hz AC Supply
Voltage Range	: 160V to 250V (1 Phase) 300V to 440V (3 Phase)

Openwell Submersible Pumps

SALIENT FEATURES

1. Design for wide voltage range.
2. Design for underwater Application.
3. Light weight & easy to install
4. Full Stainless steel stator tube as well as stainless steel shaft.

TECHNICAL SPECIFICATION

Head Range	: 8 to 56 Meter.
Discharge Range	: 20 to 1050 LPM
Motor Rating	: 0.5HP to 5HP (Single Phase) 0.5HP to 7.5HP (Three Phase)
Voltage Range	: 160V to 250V (1 Phase) 300V to 440V (3 Phase)



AQUA1 brand make highly efficient durable and best Quality openwell submersible pump.